



Parking Garage Luminaire



Suitable for wet locations
Lamp included
IP55 Listed



PGL Specification

The North Star Parking Garage Luminaire is designed for use in areas where low mounting height restrictions demand a fixture with uniform distribution and low glare cut-off illumination. The unit is rated IP55 to prevent contaminants such as dust, bugs and moisture from entering the fixture.

Basic Product Description

Heavy duty die-cast aluminum housing with one piece anodized aluminum reflector and clear acrylic lens with generous up-light, permanently sealed for trouble-free operation.

Ballast Characteristics

The Parking Garage Luminaire shall contain a long lasting, U.L. recognized High Power Factor (HPF) ballast. Will start lamps at -20°F (-30°C) for metal halide and -40°F (-40°C) for high pressure sodium. Mercury vapor lamps may be used in 175 watt metal halide fixtures. For availability of 220/240V 50Hz ballasts - consult factory.

Reflector/Refractor

One piece anodized aluminum reflector is engineered for maximum efficiency and uniform cutoff distribution. Refractor is of clear acrylic and designed to provide generous up-light and low glare illumination.

Mounting

J-Box
Balanced Pendant
Ceiling thru-wire

Applications

Parking garages, parking entrances, walkways, underpasses, loading docks, or any low ceiling areas where uniform cutoff illumination is required.

Ordering Example

Unit PGL	Wattage 1	Lamp Type H	Voltage 60Hz	Accessories SIF
Parking	0 - 70	H - Metal Halide	120	KS - Key Hole Slot
Garage	1 - 100	LS - High Pressure Sodium	208	FB - Filter Breather
Luminaire	2 - 150	PS - Pulse Start Metal Halide	240	SIF - Single Inline Fuse (120,277V)
	3 - 175	CFL - Compact Fluorescent*	277	DIF - Double Inline Fuse (208,240,480V)
	200 - 200PS	IL - Induction Lamp*	480V	EM - Emergency Quartz Relay and Socket
			4MT	EM60 - Emergency Quartz Delay Relay and Socket
			(120,208,240,277)	QS - Quartz Socket only - auxiliary power req'd.
				3CPLG - 3' cord w/locking plug
				WG - Wire Guard (OD & FL only)
				MH 3/4 - 3/4" Male Hook
				ML 3/4 - 3/4" Male Loop
				MPH 3/4 - 3/4" Power Hook

*Consult Factory for available wattages

