

Product # \_\_\_\_\_ Type \_\_\_\_\_ Date \_\_\_\_\_

Project Name \_\_\_\_\_

Project Location \_\_\_\_\_ Prepared By \_\_\_\_\_

# Smart™ Flood 100

## Smart™ Light Specifications

The 100 watt Smart™ Flood is designed to replace HID light sources of up to 250 watts. This is accomplished with sealed high brightness light modules with precision control TIR type optics. Adjustable mounting yoke included standard. Three available mounting options.

### Construction

Housing is die-formed made from low-copper 5052 aluminum, heavy duty, structurally rigid and vibration resistant. Heatsink fins are 0.040" thick made from low copper aluminum 5052 alloy with maximum contact with the housing for maximum heat dissipating surface area for the efficient cooler operation.

### Optics/Lens

The 100 watt Smart™ Flood contains 2 - 50 watt IP67 sealed light module and are easily replaceable. Modules are available in 30 degree, 45 degree (standard) and 85x135 degree (optional) beam patterns.

### Electrical

High power Cree XT-E LED source, with performance of greater than 90 lumens per watt. Standard Color Temperature 5000K, CRI of 70 or greater. Other optional color temp and CRI available on request. LED Drivers: UL/CSA recognized component to meet UL8750 & EN61347 (USR/CNR - E328335). Suitable for input power at 100-277VAC, Minimum power factor >0.95 with an operating temperature range of -22-140 degrees F / 30-60 degrees C. Dimmable and motion sensor control compatible.

### Finish

Gloss Black finish is standard. Other optional finishes available on request.

### Warranty and Certifications



5 years for LED Light Engine and Driver, 7 years for housing. 50,000 hours @ 25°C L70 LED Illumination per LM-80. cULus Wet Locations in compliance with UL 1598 and CSA C22.2 NO. 250.0 standards. IP65, IP67 upgrade option. Suitable for indoor/outdoor wet or damp location use. DLC listed and Lighting Facts.



### Dimensions

15.7 x 15.7 x 7.1 inches

EPA: 3.2



Weight: 16.3lbs. (7.4kg)



## Ordering Guide

MODEL	TOTAL LED POWER	CCT COLOR TEMP	LIGHT BEAM SPREAD	INPUT VAC	LIGHTING CONTROL	GLARE CONTROL	MOUNTING
SMF	100 100 = 100W	50 27-2700K* 30-3000K* 40-4000K* 50 - 5000K Standard *+/-350K	5 4 = NEMA 4HX4V 5 = NEMA 5HX5V 6 = NEMA 5HX7V	U U = Universal 100V to 277V 48 = 480V	D ND = Non Dimming D = Dimming	**Consult factory for available options	SM SF = Slip Fitter Mount SM = Surface Mount


Note: Due to continued efforts to improve our products, specifications are subject to change without notice.




# Smart™ Flood 100

## Photometrics

### 85/135 Degree Lens (clear frosted) NEMA Type 6



— 0.0~180.0  
— 90.0~270.0




Mounting Hight 6m, 0 Tilt,  
50LUX-5LUX

#### Illumination-85/135 Degree Beaming Angle


Height	Rectangular Light Spot	LUX
5m	9x24m	82LUX
6m	11x29m	60LUX
7m	13x34m	45LUX
8m	14x39m	35LUX
9m	15x43m	28LUX

Beam Angle (50% max)	85x135 DEG
Field Angle (10%)	130x150 DEG
Luminous Flux (IES)	9,199 lm
Light Efficacy (IES)	91 lm/W
NEMA Type	7H x 7V
BUG Rating	B3-U2-G3
UGR	16/29
IES Classification	Type II
Cutoff Classification	Semi-Cutoff

### 45 Degree Lens NEMA Type 5



— 0.0~180.0  
— 90.0~270.0




Mounting Hight 8m, 60 Tilt,  
50LUX-5LUX

#### Illumination-45 Degree Beaming Angle


Height	Beam Diameter	LUX
10m	φ 8m	155LUX
15m	φ 12m	70LUX
20m	φ 17m	38LUX
25m	φ 21m	25LUX
30m	φ 25m	17LUX

Beam Angle (50% max)	45 DEG
Field Angle (10%)	73 DEG
Luminous Flux (IES)	9,621 lm
Light Efficacy (IES)	94 lm/W
NEMA Type	5H x 5V
BUG Rating	B4-U1-G1
UGR	12
Cutoff Classification	Cutoff

### 30 Degree Lens NEMA Type 3



— 0.0~180.0  
— 90.0~270.0



Mounting Hight 12m, 60 Tilt,  
50LUX-5LUX

#### Illumination-30 Degree Beaming Angle


Height	Beam Diameter	LUX
15m	φ 8m	167LUX
20m	φ 11m	94LUX
25m	φ 13m	60LUX
30m	φ 16m	42LUX
35m	φ 19m	30LUX

Beam Angle (50% max)	35 DEG
Field Angle (10%)	48 DEG
Luminous Flux (IES)	9,644 lm
Light Efficacy (IES)	94 lm/W
NEMA Type	3H x 3V
BUG Rating	B5-U1-G0
UGR	12
Cutoff Classification	Cutoff





# Smart™ Flood 100

## Mounting Options



Surface Mount



Slip Fitter Mount

